

MAGLATCH

Compliance Without Compromise



MagLatch 91 for HK91 and 91 clones

MagLatch has two modes. Free State and Ban State. MagLatch is to be used in Ban State mode when under state regulation that prohibits detachable magazines with "evil features." Evil features include but are not limited to pistol grips, collapsible stocks, or flash hiders. To switch between modes simply field strip and rotate MagLatch 91 to the designated mode. **Radius facing receiver** is Ban State mode. **Radius facing away from receiver** is Free State mode. If using Free State mode while in a ban state you have constructed an illegal "Assault Weapon." By installing this device, the user of this product assumes all risks and liabilities. MagLatch and its affiliates are not responsible for the action or improper use of this product by the user.

MagLatch has not been approved by the CA DOJ. This device is designed to conform to the law as written in SB-880/AB 1135 which would define "fixed magazine" to mean an ammunition feeding device contained in, or permanently attached to, a firearm in such a manner that the device cannot be removed without disassembly of the firearm action.

INSTALLATION INSTRUCTIONS

Please read through all of the instructions before attempting install.

If necessary consult a qualified gunsmith to complete the install.

Before beginning, make sure your firearm is unloaded and chamber is clear.

To work properly the following items need to be installed and are not included in the kit: OEM magazine release button, bushing, and roll pin. These items must be installed prior to installing MagLatch 91. Most manufacturers included these components inside of the case or bag that your firearm came with. Or if you purchased your rifle after SB880 restrictions your firearm should already have the OEM components installed. Please see our website for links to purchase these items if needed.

- If present remove your bullet-button magazine release and install OEM components.
 - Field strip your firearm. If unsure, check YouTube for instructions and to familiarize yourself with your firearm.
 - Remove bullet-button shroud, roll pin, and bushing.
 - Reinstall spring, OEM bushing, OEM button, and OEM roll pin.
- Insert your 91 magazine.
- Install MagLatch 91 into the magazine release button roll pin (figure 1) with the radius facing the receiver as seen in Figure 4.
- Reassemble trigger pack and end plate, stock or brace. Insert take down pins.
- Installation is now complete!



Figure 1

MODES OF MAGLATCH 91:

- To switch between the modes of MagLatch begin by removing the take down pins.
- Separate the trigger pack from the receiver.
- Rotate MagLatch 91 to whichever mode is required.



Figure 3 - FREE STATE
RADIUS UP



Figure 4 - BAN STATE
RADIUS DOWN