

# MAGLATCH

Compliance Without Compromise



MagLatch Saiga Shotgun / VEPR 12

MagLatch has two modes. Free State and Ban State. MagLatch is to be used in Ban State mode when under state regulation that prohibits detachable magazines with "evil features." Evil features include but are not limited to pistol grips, collapsible stocks, or flash hiders. To switch between modes simply remove the gas adjustment screw and remove Gas Tube Plug, insert your OEM piston, and reinstall the gas adjustment screw. Use **with the Gas Port Plug** is Ban State mode. Use **without the Gas Port Plug** is Free State mode. If using Free State mode while in a ban state you have constructed an illegal "Assault Weapon." By installing this device, the user of this product assumes all risks and liabilities. MagLatch and its affiliates are not responsible for the action or improper use of this product by the user.

MagLatch has not been approved by the CA DOJ. This device is designed to conform to the law as written in SB-880/AB 1135 which states: "Semiautomatic" means a firearm functionally able to fire a single cartridge, eject the empty case, and reload the chamber each time the trigger is pulled and released. Further, certain necessary mechanical parts that will allow a firearm to function in a semiautomatic nature must be present for a weapon to be deemed semiautomatic. A weapon clearly designed to be semiautomatic but lacking a firing pin, bolt carrier, gas tube, or some other crucial part of the firearm is not semiautomatic for purposes of Penal Code sections 30515, 30600, 30605(a), and 30900.

## INSTALLATION INSTRUCTIONS

Please read through all of the instructions before attempting install.

If necessary consult a qualified gunsmith to complete the install.

Before beginning, make sure your firearm is unloaded and chamber is clear.

### Saiga Shotgun Installation

- Remove dust cover, recoil spring, and bolt assembly.
- Remove gas stopper or gas adjustment screw.
- Remove piston. A cleaning rod may be necessary to push the piston out.
- Clean the gas block tube if necessary. Avoid cleaner or lubricant from seeping into the gas port. Dry completely before proceeding.
- Insert MagLatch Gas Port Plug with flat side facing the muzzle. Figure 1.
- Reinstall gas stopper. Thread in all the way. Once bottomed out back out to next available gas setting.
- Reinstall bolt assembly, recoil spring, and dust cover.



Figure 1

### VEPR 12 Installation

- Remove dust cover, recoil spring, and bolt assembly.
- Remove gas tube.
- Remove piston. Use of the notch in the bolt can assist in removing the piston if necessary.
- Clean the gas block tube if necessary. Avoid cleaner or lubricant from seeping into the gas port. Dry completely before proceeding.
- Insert the Gas Port Plug with the flat side facing the muzzle. Figure 2.
- Reinstall gas tube.
- Reinstall bolt assembly, recoil spring, and dust cover.



Figure 2

### MODES OF MAGLATCH AK:

- BAN STATE: MagLatch Gas Port Plug installed.
- FREE STATE: OEM Piston installed.